



THIRD ANGLE PROJECTION

DIMENSIONS IN mm




DO NOT SCALE




OPTIONAL ALARM TERMINALS

OPTIONAL BACKLIGHT TERMINALS

TERMINAL CONNECTIONS:



MOUNTING DIMENSIONS:  
4 OFF  $\phi 6.5$ mm CLEARANCE HOLES  
SUITABLE FOR SCREWS WITH HEAD  $\phi 10$ mm MAX.  
(M5 PAN HEAD OR M6 CHEESE HEAD)




REAR VIEW OF FRONT  
SHOWING TERMINAL CONNECTIONS  
ALARM & BACKLIGHT ARE OPTIONAL

VIEWS OF REAR CASE WITH FRONT REMOVED

CABLES TO UNIT TERMINALS


OPTIONAL TERMINAL BOARD

CONDUIT BONDING PLATE WITH M4 EARTH STUD



WITH OPTIONAL TERMINAL BOARD

ISOLATED SCREEN STUD M4



WITH ISOLATED STUD FOR CABLE SCREENS

NOTE:  
TERMINALS 2 & 4 ARE INTERNALLY LINKED FOR JOINING RETURN WIRES.

FOR OPTIONAL TERMINAL BOARD ONLY:  
TERMINALS E ARE INTERNALLY CONNECTED TO THE ENCLOSURE.  
TERMINALS 5 & 6 ARE INTERNALLY LINKED FOR JOINING CABLE SCREENS

|      |            |                             |      |       |
|------|------------|-----------------------------|------|-------|
| 2    | 11.04 2017 | CRN1613. Screen stud added. |      |       |
| 1    | 28.04 2016 | P0172. First release.       | .    | .     |
| Iss. | Date       | Modification                | Ckd. | Appd. |

**BEKA associates**  
Hitchin England  
company confidential, copyright reserved.

Title

CUSTOMER DRAWING for  
BA324G 5 DIGIT I.S. INDICATOR  
IN FIELD MOUNTING ENCLOSURE

Drawn

RC

Checked

.

Scale

N/A

Drawing No.

Sheet 1 of 1

CD324G